



## Silica Flour 35/200S

Silica Flour 35/200S is a milled natural rock mineral silica sand with the following typical properties.

### GRADING

- 250 microns	100.00 %
- 212 microns	99.94 %
- 180 microns	99.86 %
- 150 microns	96.71 %
- 106 microns	85.39 %
- 75 microns	70.43 %
- 53 microns	56.56 %

### CHEMICAL ANALYSIS

Silica	SiO <sub>2</sub>	99.00 %
Titania	TiO <sub>2</sub>	0.13 %
Alumina	Al <sub>2</sub> O <sub>3</sub>	0.38 %
Ferric Oxide	Fe <sub>2</sub> O <sub>3</sub>	0.06 %
Lime	CaO	0.03 %
Magnesia	MgO	0.02 %
Potash	K <sub>2</sub> O	0.09 %
Soda	Na <sub>2</sub> O	0.05 %
Loss on Ignition		0.19 %

The data given on this sheet is based on test results believed to be representative of the product and should not be interpreted as a binding specification.

Richard Baker Harrison Ltd.  
253 Cranbrook Road  
Ilford, Essex.  
IG1 4TQ  
U.K.



GB94/3715

Tel : +44 (0)20 8554 0102  
Telefax : +44 (0)20 8554 9282  
E-mail : rbhltd@aol.com  
www : rbhltd.com