



CAS-Nr. 9004-34-6

ECS-Nr. 232-679-9

TECHNOCEL[®] 1004-6N**Product description:**

Functional filler of technical raw cellulose

Characteristic	Value	Unit
Appearance	grey fiber	
Loose density	50 - 90	g/l
Loss on drying	Max. 6.0	%
pH value	6.0 - 9.0	
Screen analysis (Alpine Air Draught Sieve)		
Bigger than 32 µ	< 90	%
Bigger than 200 µ	< 30	%
Bigger than 800 µ	< 10	%

Shelf life: 5 years, provided that the goods are stored in a dry and cool place.**Applications**

All TECHNOCEL[®] products are totally harmless from the environmental as well as industrial medicine point of view and they are all made of renewable resources. The technical functions in the different applications are mainly thixotroping, reinforcement and adsorbing. Furthermore TECHNOCEL[®] is used as carrier and filler.

The specified data serve as technical information and are based on average values of the current production.

For further information about the application, please contact our customer service:

Phone: +49-36783-882-0

Fax: +49-36783-882-252

Internet: www.cff.de

email: cff@cff.de



DIN EN ISO 9001:2000
Zertifikat: 01 100 035087

CFF GmbH & Co. KG

Arnstädter Str. 2
D-98708 Gehren